

SVR-8008LT1



Product Summary

- 5MP, 4MP, 3MP (Half Resolution) / 2MP, 960H
- 1 HDMI, 1 VGA, 4ch/8ch :1 BNC,16ch : 1 D-SUB
- UHD, QHD, FHD, SXGA, XGA
- H.265, H.264
- 5MP, 4MP, 3MP (Half Resolution) / 2MP, 960H
- 1 HDMI, 1 RCA
- 2 x USB 2.0
- 10fps (5MP), 15fps (2MP)

Major Specifications

Model Name		SVR-8008LT1
Video	Input	8 BNC, IP
	Input Resolution	5MP, 4MP, 3MP (Half Resolution) / 2MP, 960H
	Output	1 HDMI, 1 VGA, 4ch/8ch :1 BNC,16ch : 1 D-SUB
	Output Resolution	UHD, QHD, FHD, SXGA, XGA
Recording	Speed	2MP : 15fps/ch 5MP, 4MP, 3MP : 15fps/ch (Half Resolution)
	Compression	H.265, H.264
	Resolution	5MP, 4MP, 3MP (Half Resolution) / 2MP, 960H
Playback	Speed	2MP : 104 fps Half 3MP : 73 fps Half 4MP : 117 fps Half 5MP : 86 fps
	Resolution	5MP, 4MP, 3MP (Half Resolution) / 2MP, 960H
Audio	Input	8 RCA
	Output	1 HDMI, 1 RCA
Interface	Senser In / Out	8 / 1 - NC / NO
	USB	2 x USB 2.0
	PTZ / Keyboard	RS485 - Terminal Block
	ATM / POS	Ethernet POS
Network	Compression	H.264, H.265, JPEG
	Speed	10fps (5MP), 15fps (2MP)
	Resolution	Normal 2MP, REC Video Bypass Max. 5MP(Half)
System	OS	Embedded Linux (Built-in Flash Memory)
	Pre / Post-Alarm	5sec /5sec~5min
	Recording Mode	Continuous, Event, Schedule
	Data Search	Calendar, Multi Day / Time, Event, Go to Time
	Backup Interface	USB, Network
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data
	Alarm Action	Buzzer, PTZ Preset, E-mail, SPOT, Relay, Event Popup, Push
	User	15 Users (Admin, User1 ~User14)
	Network Viewer	NETUS-Pro, Web Viewer, SmartEyesPro(iOS, Android), S-CCTV Viewer(iOS, Android)
Storage	ONVIF	ONVIF Profile T
	Primary	1 HDD
General	Size (W x H x D)	300 x 53 x 208 mm
	Weight(w/o HDD)	1.1 kg
	Temp / Humidity	5 ~ 40°C /10% ~80%
	Power Supply	12V / 2A
	Consumption	60 Watts